

⑫

EUROPEAN PATENT APPLICATION

⑲ Application number: **88303760.8**

⑤① Int. Cl.⁴: **G 01 N 27/40**
// G01N33/49

⑳ Date of filing: **26.04.88**

③① Priority: **27.04.87 GB 8709882**

④③ Date of publication of application:
02.11.88 Bulletin 88/44

⑧④ Designated Contracting States:
CH DE FR GB IT LI NL SE

⑦① Applicant: **MediSense, Inc.**
128 Sidney Street
Cambridge Massachusetts 02139 (US)

⑦② Inventor: **Wickham, Mark David**
12, Summerfields
Abingdon Oxon, OX14 2PG (GB)

Morris, Richard Alan
31, Franklyn Close Hunters Knoll
Abingdon Oxon, OX14 1YF (GB)

⑦④ Representative: **Ruffles, Graham Keith et al**
MARKS & CLERK 57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

The title of the invention has been amended (Guidelines for Examination in the EPO, A-III, 7.3).

⑤④ **Electrochemical sensor with red blood cell exclusion layer.**

⑤⑦ An electrochemical sensor is provided for use with whole blood in order to effect an electrochemical measurement. The sensor has a an exclusion layer excluding at least red blood cells from contact with sensor electrodes of the sensor.

Description

IMPROVED MEMBRANE CONFIGURATIONS

BACKGROUND OF THE INVENTION

The present invention relates to improved membrane configurations for use in electrochemical sensors intended for use with whole blood.

Electrochemical sensors, especially amperometric electrochemical sensors of the kind described for instance in EP 127958, when contacted with blood, can detect very specifically one or more analytes present in the blood. Such sensors are based on enzyme and/or mediator systems, and can be used to detect, for example, naturally occurring metabolites such as glucose or cholesterol, or substances introduced to the body such as alcohol or drugs. In a typical mode of use, the system is set up so that there is a response at the amperometric electrochemical sensor which is dependent on the concentration of test substance.

Whole blood is a complex mixture, predominantly aqueous, containing dissolved gases, simple dissociated and hydrated ions, materials in colloidal or otherwise complex solution, small scale cellular debris, and living cellular components. It is therefore sometimes difficult to achieve reproducible results when using whole blood samples.

SUMMARY OF THE INVENTION

In a first aspect, the present invention provides an electrochemical sensor for contact with whole blood in order to effect an electrochemical measurement. The electrochemical sensor has at least one exclusion layer excluding at least red blood cells from contact with the sensing electrodes of the sensor.

We have realised that an improved system for the testing of whole blood enables a sensor to be contacted with the blood and permits internal sensor electrodes to record (either in a usable initial period or more permanently) the existence, amount, or continuing level of the analyte in the blood. In the present invention, the exterior of the sensor is exposed to whole blood but the sensor electrodes are exposed only to serum.

The main advantages for detection in serum rather than in whole blood are:-

1. Red blood cells themselves, and specifically the surface of the red blood cells or substances contained within them, may interfere with the electrochemical reaction.

2. Red blood cells, which are complex entities readily capable of agglutinating and coating, may bond to the conductive electrode surfaces, whereby the surface is partially coated and blocked off from its surroundings and measurement is affected.

3. Diffusion coefficients for substances in serum are normally higher than in whole blood, giving higher measurement currents and potentially more accurate testing with a steeper calibration curve.

PREFERRED EMBODIMENTS

The electrochemical sensor is preferably one which involves amperometric detection, and is preferably a strip sensor, especially a throw-away dry strip sensor. Accordingly the sensor electrodes preferably comprise electrode areas formed for instance by screen printing or other suitable technique. Reference is made to EP 127958, 184895, 230786, among other published European Patent Specifications in the name of MediSense Inc (formerly Genetics International Inc), and these texts are incorporated herein.

The sensor electrodes include a reference electrode (for example a silver, silver chloride electrode) and an active electrode (for example an electrode for detecting glucose, using for instance glucose oxidase and a suitable mediator substance such as a ferrocene, or for detecting other substances, such as cholesterol, paracetamol, salicylate, etc).

As will be described below in more detailed examples of the exclusion layer include a thin solid layer, flexible or otherwise, or a void-containing layer, especially with intercommunicating voids, even if generally fibrous or similarly discontinuous in its solid phase.

Preferably the exclusion layer is such as to exclude many live cellular components, and most preferably it excludes cellular debris and like solid particles, allowing only dissolved or colloidal materials to pass through.

In one form of carrying out the present invention, there is provided an electrochemical sensor having laminated thereto, cast thereon, or layered thereover an exclusion layer in the form of a membrane which excludes red blood cells.

In this aspect the invention involves the use of a membrane which is such as to transmit serum to the sensor electrodes but which has sufficiently small pores to exclude red blood cells. Such a membrane typically consists of a synthetic polymeric material. It can be preformed as one or more sheets, or it can be laminated in situ. It can also be cast directly on to the electrodes from solution or from a melt.

A phase-inversion microporous membrane or a track etched membrane is preferred.

A phase-inversion microporous membrane can be prepared by dissolving a polymer in a solvent/non-solvent mixture, possibly with other additives, and thereafter leaving the solvent portion to evaporate. The polymer forms a porous structure over the adjacent surfaces, the porosity of which can be controlled by adjustment of the casting solution composition and the evaporating conditions.

A track etched membrane, such as a Nuclepore (Trade Mark) polycarbonate or polyester membrane, is commercially available and is made by irradiation and etching to yield a thin, microporous membrane with geometric, capillary shaped pores and smooth flat faces.

The invention further extends to a dry strip electrochemical sensor which is a laminate structure

(being a laminate in a general sense to include layered or stratified structures not necessarily prepared by a step of lamination) with an exclusion membrane and a layer of material containing intercommunicating voids. The membrane serves to exclude red blood cells. In the laminate structure, the sequence of layers can be membrane-voids material-electrodes, or voids material-membrane-electrodes.

In one version, this invention thus provides a laminate structure in which a membrane excluding red blood cells is laminated upon or cast upon or layered over a layer of material containing intercommunicating voids, which material is itself layered on the sensor electrode surfaces. The material with the intercommunicating voids can for example be a fibrous, spongy or woven material. In effect, this aspect of the invention provides a reservoir of serum occupying the communicating voids of the material and available at the electrode surfaces. The test substance effectively diffuses through serum and not through the whole blood, as a consequence of which higher detection currents are achieved.

Capillary action exerted by the material with these continuous voids may also assist in drawing serum through the membrane to leave the red blood cells on the further side. Possible materials for use in this embodiment include synthetic polymeric foams with intercommunicating cells, whether of a rigid or resilient nature, pads of fibrous material, especially material with inert fibers such as glass fibers, or woven inert material made e.g. from glass or synthetic polymer.

In an alternative version, the layer of material containing intercommunicating voids is layered or laminated on the membrane excluding red blood cells, which membrane is itself cast, laminated or layered on the electrode surfaces. In this construction, the voids material acts as a pre-filter and slows down the progress of red blood cells sufficiently to prevent blocking of the membrane pores. In this way there is sufficient time for adequate serum to permeate through the membrane.

In a third aspect of the invention the surface of the sensor electrodes is covered with a material serving as the exclusion layer but having interconnecting voids of a size suitable to delay arrival of at least red blood cells to the active surface or reference surface.

The actual materials which may be used can resemble those used in the second embodiment as discussed above. The mode of action of this embodiment is not to exclude the red blood cells permanently, but to ensure that there is a period available for measurement at which the only material seen by the electrode surface is effectively serum. Thus, in practice, there would be an initial response of a relatively high current for detection, representing the serum concentration, and a lower eventual response as red blood cells find their way through the intercommunicating voids to the electrode surface.

SPECIFIC EMBODIMENTS

The invention will be further described first with reference to Figures 1 to 3 of the accompanying drawings, in which:

Figure 1 shows in diagrammatic cross-section a first embodiment of the invention;

Figure 2 shows in similar section a second embodiment; and

Figure 3 shows in similar section a third embodiment.

Figure 1 shows an amperometric dry strip disposable sensor with an electrode surface 1 covered immediately with a membrane 2 of for example synthetic polymeric material, laminated or cast thereon as a sheet. A sample in the form of a drop of blood 3 is placed upon the membrane, but the membrane 2 is of such a nature that only the serum components of the blood sample can penetrate and reach the electrode surface.

Such a configuration is used if red blood cell exclusion only is required, that is to say if the red blood cells contain or have on their surface substances which might interfere with the electrochemical reaction. An increase in current over that observed when using the non-protected electrode is to be expected, because the test substance is still diffusing from the whole blood through the membrane to the electrode surface.

Figure 2 shows a second embodiment of the invention. The same reference numerals as used in Figure 1, except that an additional layer 4 is provided of a fibrous or cellular material containing intercommunicating voids, which can fill and intercommunicate to provide an actual serum reservoir between the membrane and the electrode surface.

This configuration of Figure 2 not only acts as a barrier to red blood cells, but increases the detection signal because of the existence of an actual body of serum and because of the different diffusion coefficient through that serum.

Figure 3 shows a modified embodiment in which the continuous polymeric membrane is absent. However, the filter element 4 is of such a nature as to provide, at least temporarily, the function of an exclusion layer. Although red blood cells can eventually penetrate this type of layer, they traverse it considerably more slowly than the serum and the dissolved components so that at least for an initial period the electrode surface sees only serum and can take measurements accordingly. Such a configuration would be useful when an increase in signal is required, but when it is not essential for other reasons to exclude all red blood cells.

Further variations are possible. For instance, considering the embodiment of Figure 2, the positions of the membrane 2 and layer 4 can be inverted giving a laminate where the layer 4 acts a pre-filter for the membrane 2, and prevents clogging of the membrane surface.

The present invention is further illustrated by the following Examples, in which reference is made to Figures 4 and 5 of the accompanying drawings, in which:

Figure 4 is a plot of current against paracetamol concentration for a paracetamol sensor of

this invention, and

Figure 5 is a plot of current against glucose concentration for a glucose sensor of this invention.

Example 1

Membranes Were placed on filter paper and 25 μ l of whole blood was placed on the membranes. After 15 seconds, the membranes were removed and the quantity of serum which had passed through to the filter paper was weighed.

Most membranes have a shiny surface and a matt surface, due to production characteristics. The sides usually have different filtration properties, and this factor was investigated.

As a result, it was established that Nuclepore polycarbonate membranes, shiny face upward, with pore diameter of 1.0 μ m. 0.8 μ m and 0.6 μ m gave suitable results.

Example 2

Using the Nuclepore polycarbonate 0.8 μ m membrane, it was then found that various pre-filters could be overlaid, such as Nuclepore P300 filled or unfilled prefilter. and Sartorius SM13400 prefilter.

Example 3

The following phase inversion membranes were shown to give good plasma separation from 25 μ l whole blood, when used in conjunction with the Nuclepore P300 filled prefilter:

0.1 μ m	Micron Separations Inc	Nylon Membrane
0.45 μ m	Micron Separations Inc	Nylon Membrane
1.2 μ m	Schleicher & Schuell ME28	Cellulosic Esters
1.2 μ m	Schleicher & Schuell ST69	Cellulosic Esters
0.8 μ m	Schleicher & Schuell ST68	Cellulosic Esters
0.8 μ m	Schleicher & Schuell ST27	Cellulosic Esters
3.0 μ m	Schleicher & Schuell ME29	Cellulosic Esters
0.6 μ m	Schleicher & Schuell BA90	Cellulosic Esters
5.0 μ m	Millipore SMWP 04700	Cellulosic Esters
8.0 μ m	Millipore SCWP 04700	Cellulosic Esters

Example 4

The usual whole blood response of paracetamol sensors (EP 184895) is a dog-leg shape for charge passed plotted against paracetamol concentration. However the serum response is a linear response and consequently easier to use in analogue devices.

The results of Figure 4 show that when the 0.8 μ m polycarbonate Nuclepore membrane and prefilter were used on paracetamol electrodes, the linear response was achieved with whole blood indicating serum separation.

Example 5

The main advantage of serum separation is that the electrodes give a higher response in serum than whole blood. The higher response (μ amps) gives rise to a higher slope for charged pass versus concentration of analyte. The higher slope and decreased intercept in turn give rise to greater precision.

The following results for glucose sensors show that the Nuclepore polycarbonate membrane, when used with a prefilter, led to an increased slope compared with data obtained using control sensors (without a membrane or prefilter) and whole blood. The intercept also decreased in some cases, which shows that serum separation is taking place.

Control Sensors (Whole Blood 25 μ l)
slope = 6.15598 intercept = 25.06888

Control Sensors (serum 25 μ l) slope = 18.408 intercept = 32.454

Sensors 0.8 μ m Membrane/Prefilter (Whole Blood 25 μ l)
slope = 14.473 intercept = 22.050
(The results for this experiment were plotted to give Figure 5.)

Sensors 1.0 μ m Membrane/Prefilter (Whole Blood 25 μ l)
slope = 12.953 intercept = 33.730

Example 6

The response shown by cholesterol sensors (EP230786) tend to become saturated and it is often difficult to delineate different cholesterol concentrations.

The following results show that serum separation is taking place when the membrane and prefilter are attached (though the system tends to saturate above 10mM cholesterol).

Results to 10 mM Cholesterol: 25 μ l Whole Blood
Control Sensors
slope = 0.924 intercept = 4.632

25 μ l Serum (Serum optimized Sensors)
slope = 2.615 intercept = 14.584

25 μ l Blood (Serum optimized Sensors + membrane/prefilter)
slope = 2.127 intercept = 8.463

Claims

1. An electrochemical sensor for contact with whole blood in order to effect an electrochemical measurement, which has an exclusion layer excluding at least red blood cells from contact with sensor electrodes of the sensor.

2. The sensor of claim 1, which is a

disposable strip sensor for amperometric detection of an analyte.

3. The sensor of claim 1, wherein said exclusion layer includes a membrane selected from the group consisting of a phase-inversion microporous membrane and a track etched membrane.

5

4. The sensor of claim 1, which has a multilayer construction comprising said exclusion layer and a layer of material containing intercommunicating voids.

10

5. The sensor of claim 4, in which the sequence of layers is membrane-voids material-electrodes.

6. The sensor of claim 4, in which the sequence of layers is voids material-membrane-electrodes.

15

7. An amperometric throw-away strip sensor comprising a laminate structure in which a membrane excluding red blood cells is laminated upon or cast upon or layered over a layer of material containing intercommunicating voids, which material is itself layered on an area of sensor electrodes.

20

8. An amperometric throw-away strip sensor comprising a laminate structure in which a layer of material containing intercommunicating voids is layered or laminated on a membrane excluding red blood cells, which membrane is itself cast, laminated or layered on an area of sensor electrodes.

25

30

9. An amperometric throw-away strip sensor in which an area of sensor electrodes is covered with a material serving as an exclusion layer and having interconnecting voids of a size suitable to delay arrival of at least red blood cells to the sensor electrodes.

35

10. In an amperometric method for detection of an analyte in whole blood using a dry strip sensor electrode system, the improvement which consists of using an exclusion layer to exclude red blood cells from contact with the sensor electrodes.

40

45

50

55

60

65

5

0289269




FIG. 1.




FIG. 2.




FIG. 3.

0289269




FIG.4.




FIG.5.

12

EUROPEAN PATENT APPLICATION

21 Application number: 88303760.8

51 Int. Cl.⁵: **G01N 27/40, //G01N33/49**

22 Date of filing: 26.04.88

30 Priority: 27.04.87 GB 8709882

43 Date of publication of application:
02.11.88 Bulletin 88/44

64 Designated Contracting States:
CH DE FR GB IT LI NL SE

68 Date of deferred publication of the search report:
04.07.90 Bulletin 90/27

71 Applicant: MediSense, Inc.
128 Sidney Street
Cambridge Massachusetts 02139(US)

72 Inventor: Wickham, Mark David
12, Summerfields
Abingdon Oxon, OX14 2PG(GB)
Inventor: Morris, Richard Alan
31, Franklyn Close Hunters Knoll
Abingdon Oxon, OX14 1YF(GB)

74 Representative: Ruffles, Graham Keith et al
MARKS & CLERK 57-60 Lincoln's Inn Fields
London WC2A 3LS(GB)

54 **Electrochemical sensor with red blood cell exclusion layer.**

57 An electrochemical sensor is provided for use with whole blood in order to effect an electrochemical measurement. The sensor has a an exclusion layer excluding at least red blood cells from contact with sensor electrodes of the sensor.

EP 0 289 269 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 88 30 3760

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
X	US-A-3979274 (D.P.NEWMAN) * column 3, lines 30 - 63; figures 1, 2 * * column 5, lines 7 - 30 * ----	1, 3, 4, 6, 9, 10	G01N27/40 //G01N33/49
X	EP-A-25110 (TOKYO SHIBAURA DENKI KABUSHIKI KAISHA) * page 8, line 15 - page 9, line 37; figure 1 * ----	1, 3-5	
X	EP-A-207370 (MILES LABORATORIES INC.) * page 5, line 26 - page 6, line 11 * * page 15, lines 14 - 28; figures 3, 4 * ----	1-3, 6, 9, 10	
X	WO-A-8502257 (SENTECH MEDICAL CORP.) * page 12, line 1 - page 13, line 18; figures 1, 2 * ----	1-4, 6, 8	
D,X	EP-A-127958 (GENETICS INTERNATIONAL INC.) * page 23, line 16 - page 24, line 11; figures 1-4 * ----	1-3, 9, 10	
P,X	EP-A-230472 (MATSUSHITA ELECTRIC INDUSTRIAL CO.) * page 12, line 5 - page 13, line 12; figures 8, 9 * ----	1-10	TECHNICAL FIELDS SEARCHED (Int. Cl.4)
X	& WO-A-8607632 ----		G01N C12M
E	EP-A-327018 (NOVA BIOMEDICAL CORP.) * column 4, line 7 - column 5, line 38; figures 1, 2 * -----	1	
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 20 APRIL 1990	Examiner DE KOK A, J.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			



P.B.5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo.nl
FAX +31 70 340 3016

**Europäisches
Patentamt**

Zweigstelle
in Den Haag
Recherchen-
abteilung

**European
Patent Office**

Branch at
The Hague
Search
division

**Office européen
des brevets**

Département à
La Haye
Division de la
recherche

Samuels, Adrian James
Frank B. Dehn & Co.,
179 Queen Victoria Street
London EC4V 4EL
GRANDE BRETAGNE

Datum/Date

04.11.02

Zeichen/Ref./Réf. 96.75954	Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°. 00906895.8-2404-US0000620
Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire Inverness Medical Technology, Inc.	

COMMUNICATION

The European Patent Office herewith transmits as an enclosure the European search report for the above-mentioned European patent application.

If applicable, copies of the documents cited in the European search report are attached.

☒ Additional set(s) of copies of the documents cited in the European search report is (are) enclosed as well.

REFUND OF THE SEARCH FEE

If applicable under Article 10 Rules relating to fees, a separate communication from the Receiving Section on the refund of the search fee will be sent later.



**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 90 6895

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-10-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5708247	A	13-01-1998	AU 715340 B2	20-01-2000
			AU 2269297 A	02-09-1997
			CA 2245941 A1	21-08-1997
			EP 0880692 A1	02-12-1998
			US 5951836 A	14-09-1999
			WO 9730344 A1	21-08-1997
			US 6241862 B1	05-06-2001

EP 0289269	A	02-11-1988	AU 600354 B2	09-08-1990
			AU 1514888 A	27-10-1988
			EP 0289269 A2	02-11-1988
			JP 63314456 A	22-12-1988

US 5628890	A	13-05-1997	CA 2159553 A1	30-03-1997
			JP 9222411 A	26-08-1997

US 5762770	A	09-06-1998	US 5508171 A	16-04-1996
			AU 712527 B2	11-11-1999
			AU 6345196 A	05-02-1997
			CA 2224308 A1	23-01-1997
			DE 29623913 U1	07-09-2000
			DE 69617464 D1	10-01-2002
			DE 69617464 T2	29-08-2002
			DE 874984 T1	05-10-2000
			EP 0874984 A1	04-11-1998
			ES 2154250 T1	01-04-2001
			JP 2001511881 T	14-08-2001
			WO 9702487 A1	23-01-1997

US 5658444	A	19-08-1997	AU 6685694 A	12-12-1994
			CA 2162045 A1	24-11-1994
			DE 69411732 D1	20-08-1998
			DE 69411732 T2	25-02-1999
			EP 0698206 A1	28-02-1996
			WO 9427140 A1	24-11-1994

US 5951836	A	14-09-1999	US 5708247 A	13-01-1998
			US 6241862 B1	05-06-2001
			AU 715340 B2	20-01-2000
			AU 2269297 A	02-09-1997
			CA 2245941 A1	21-08-1997
			EP 0880692 A1	02-12-1998
			WO 9730344 A1	21-08-1997



European Patent
Office

**SUPPLEMENTARY
EUROPEAN SEARCH REPORT**

Application Number
EP 00 90 6895

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 708 247 A (MCALEER JEROME F ET AL) 13 January 1998 (1998-01-13) * column 2, line 3 - column 4, line 45; claims 1-34 *	1-17	G01N27/26 G01N27/30 C12Q1/00
A	--- EP 0 289 269 A (MEDISENSE INC) 2 November 1988 (1988-11-02) * column 1, line 30 - column 3, line 20 *	1-17	
A	--- US 5 628 890 A (CARTER NIGEL F ET AL) 13 May 1997 (1997-05-13) * column 2, line 40 - column 6, line 65; example 1 *	1-17	
A	--- US 5 762 770 A (HEALD BRIAN A ET AL) 9 June 1998 (1998-06-09) * column 3, line 7 - column 5, line 25 *	1-17	
A	--- US 5 658 444 A (BLACK MURDO ET AL) 19 August 1997 (1997-08-19) * column 2, line 18 - column 6, line 17 *	1-17	
P,X	--- US 5 951 836 A (SCOTT DAVID ET AL) 14 September 1999 (1999-09-14) * column 2, line 21 - column 4, line 30 *	1-17	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G01N C12Q
The supplementary search report has been based on the last set of claims valid and available at the start of the search.			
Place of search MUNICH		Date of completion of the search 21 October 2002	Examiner Diez Schlereth, D
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	